

Call Toll Free 1.866.410.CCTV (2288)
<http://www.cctvstar.com>



1/3" High Resolution CCD II, 2.8~12mm Varifocal IR
700 TV Lines, 0.01 Lux, 24 IR LEDs, Vandal Proof, D-WDR
OSD, TDN/ICR, 3D-DNR, Weatherproof, DC12V
Made in Korea

FEATURES

1/3" High Resolution CCD II, 2.8~12mm Varifocal IR
700 TV Lines, 0.01 Lux, 24 IR LEDs, Vandal Proof
D-WDR, OSD, TDN / ICR, 3D-DNR, Weatherproof, DC12V



ITEM # PVD-700HI2812

SPECIFICATIONS

Image Sensor	1/3" High Resolution CCD
Effective Pixel	768(H) x 494(V) NTSC, 752(H) x 582(V) PAL
Resolution	700 TV Lines
TV Type	NTSC, PAL
Sync. Type	Internal
Scanning System	2:1 Interlace
Video Output	1.0 Vp-p (Sync. Negative) Termination 75 Ω
Gamma Characteristic	$\gamma = 0.45$ Typ.
Min. Illumination	0.01 Lux (24 IR LED On)
S/N Ratio	52 dB or more (AGC Off)
Automatic Gain Control	OFF / LOW / MIDDLE / HIGH
Day & Night	AUTO / COLOR / BW / EXT
Shutter Speed	1/60 ~ 1/100,000 sec (NTSC) 1/50 ~ 1/100,000 sec (PAL)
Test Illuminance Area	Average test illumination by front view
Power Supply	DC12V 80mA
OSD	Available
LED	IR LED 24 EA
Lens	2.8~12mm DC Auto Iris
Operating Temp.	14 °F to 122 °F
Preservation Temp.	- 4 °F to 140 °F
Dimension	112(W)mm x 87(D)mm
Weight	Approx. 400g