

1/3" SONY Super HAD CCD II, 0.01 Lux (F/1.2), 700 TVL CS Mount, Built-in OSD, SMART 3D-DNR, DIS, WDR Day & Night (ICR), Dual Voltage Made in Korea

FEATURES

1/3" SONY SUPER HAD CCD II
Tru-700TV Lines, 0.01 Lux (F/1.2)
CS Type Mount, Built-in OSD, 3D-DNR, WDR
Motion Detection, Privacy Zone
Day & Night (ICR),
12V DC, 24V AC Dual Voltage

SPECIFICATIONS

Image Sensor	1/3" SONY Super HAD CCD II
Effective Pixel	768(H) x 494(V) NTSC
Scanning System	2:1 Interlace
Sync. Type	Internal
Resolution	700 TV Lines
S/N Ratio	52 dB or More (AGC Off)
Video Output	1.0 Vp-p (Sync. Negative) Termination 75 Ω
Min. Illumination	0.01 Lux (at F/1.2), 0.0001 Lux (Sense up)
Gamma	$r = 0.45$ Typ. (0.2~1.0)
OSD	Yes (Multi Language)
White Balance	ATW (2,500°K ~ 9,500°K) / Manual / AWC
Shutter Speed	1/60 ~ 1/100,000 sec
Sense up	Auto (Selectable limit 2X ~ 1024X) / Fixed / Off
Backlight	OFF / BLC / DWDR / HLC (On / Off)
AGC	Low / Middle / High / Off
DNR (3D)	Auto / Low / Middle / High / Off
Motion Detection	On / Off (4 Zone)
Privacy Zone	On / Off (8 Zone)
Mirror	On / Off
Day & Night	ICR / Electronic (Auto, Color, B/W)
Blemish Compensation	Auto / Off
Lens	CS Mount
Power Supply	12V DC, 24V AC Dual Voltage
Current Consumption	Max. 290mA (at 12V DC, 24V AC)
Operating Temp.	14 °F to 122 °F
Storage Temp. Range	- 4 °F to 144 °F
Dimension	1.96(W) x 2.24(H) x 3.54(D) inch
Weight	Approx. 0.66 lb



ITEM # SB-700W

